

TOSHIBA PHOTOCOUPLER GaAs IRED & PHOTO-TRIAC

TLP3020, TLP3021, TLP3022, TLP3023

OFFICE MACHINE
HOUSEHOLD USE EQUIPMENT
TRIAC DRIVER
SOLID STATE RELAY

The TOSHIBA TLP3020, TLP3021, TLP3022 and TLP3023 consist of a photo-triac optically coupled to a gallium arsenide infrared emitting diode in a six lead plastic DIP package.

- Peak Off-State Voltage : 400 V (Min.)
- Trigger LED Current : 30mA (Max.) (TLP3020)
15 mA (Max.) (TLP3021)
10 mA (Max.) (TLP3022)
5 mA (Max.) (TLP3023)
- On-State Current : 100 mA (Max.)
- UL Recognized : UL1577, File No. E67349
- Isolation Voltage : 5000 Vrms (Min.)
- Option (D4) Type
- VDE Approved : DIN VDE0884 / 08.87,
Certificate No. 68329


Maximum Operating Insulation Voltage: 630 VPK

Highest Permissible Over Voltage: 6000 VPK

Note: When a VDE0884 approved type is needed, please designate the " Option (D4) "


	7.62mm pitch standard type	10.16 mm pitch (LF2) type
● Creepage Distance :	7.0 mm (Min.)	8.0 mm (Min.)
Clearance :	7.0 mm (Min.)	8.0 mm (Min.)
Insulation Thickness :	0.5 mm (Min.)	0.5 mm (Min.)

Unit: mm



Weight: 0.44g

PIN CONFIGURATION (TOP VIEW)



- 1: ANODE
- 2: CATHODE
- 3: N.C.
- 4: TERMINAL 1
- 6: TERMINAL 2

961001EBC2

•TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

•Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.

•The products described in this document are subject to foreign exchange and foreign trade control laws.

•The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

•The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta=25°C)

CHARACTERISTIC			SYMBOL	RATING	UNIT
LED	Forward Current		I _F	50	mA
	Forward Current Derating (Ta ≥ 53°C)		ΔI _F /°C	−0.7	mA/°C
	Peak Forward Current (100μs pulse, 100pps)		I _{FP}	1	A
	Power Dissipation		P _D	100	mW
	Power Dissipation Derating (Ta ≥ 25°C)		ΔP _D /°C	−1.0	mW/°C
	Reverse Voltage		V _R	5	V
	Junction Temperature		T _J	125	°C
DETECTOR	Off-State Output Terminal Voltage		V _{DRM}	400	V
	On-Stage RMS	Ta=25°C	I _{T(RMS)}	100	mA
	Current	Ta=70°C		50	
	On-State Current Derating (Ta ≥ 25°C)		ΔI _T /°C	−1.1	mA/°C
	Peak On-Stage Current (100μs pulse, 120pps)		I _{TP}	2	A
	Peak Nonrepetitive Surge Current (P _W =10ms, DC=10%)		I _{TSM}	1.2	A
	Power Dissipation		P _D	300	mW
	Power Dissipation Derating (Ta ≥ 25°C)		ΔP _D /°C	−4.0	mW/°C
	Junction Temperature		T _J	115	°C
Storage Temperature Range			T _{stg}	−55 ~ 150	°C
Operating Temperature Range			T _{opr}	−40 ~ 100	°C
Lead Soldering Temperature (10s)			T _{sol}	260	°C
Total Package Power Dissipation			P _T	330	mW
Total Package Power Dissipation Derating (Ta ≥ 25°C)			ΔP _T /°C	−4.4	mW/°C
Isolation Voltage (AC, 1 min., R.H. ≤ 60%) (Note 1)			BV _S	5000	V _{rms}

Note 1: Device considered a two terminal device : Pins 1, 2 and 3 shorted together and pins 4 and 6 shorted together.

RECOMMENDED OPERATING CONDITIONS

CHARACTERISTICS	SYMBOL	MIN	TYP.	MAX	UNIT
Supply Voltage	V_{AC}	—	—	120	Vac
Forward Current	I_F^*	15	20	25	mA
Peak On-Stage Current	I_{TP}	—	—	1	A
Operating Temperature	T_{opr}	-25	—	85	°C

*: In the case of TLP3022


INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN	TYP.	MAX	UNIT
LED	Forward Voltage	V_F	$I_F=10\text{mA}$	1.0	1.15	1.3	V
	Reverse Current	I_R	$V_R=5\text{V}$	—	—	10	μA
	Capacitance	C_T	$V=0, f=1\text{MHz}$	—	10	—	pF
DETECTOR	Peak Off-State Current	I_{DRM}	$V_{\text{DRM}}=400\text{V}$	—	10	100	nA
	Peak On-Stage Voltage	V_{TM}	$I_{\text{TM}}=100\text{mA}$	—	1.7	3.0	V
	Holding Current	I_H	—	—	0.6	—	mA
	Critical Rate of Rise of Off-State Voltage	dv / dt	$V_{\text{in}}=120\text{Vrms}, T_a=85^\circ\text{C}$ (Fig.1)	200	500	—	$\text{V}/\mu\text{s}$
	Critical Rate of Rise of Commutating Voltage	$dv / dt(\text{c})$	$V_{\text{in}}=30\text{Vrms}, I_F=15\text{mA}$ (Fig.1)	—	0.2	—	$\text{V}/\mu\text{s}$


COUPLED ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN	TYP.	MAX	UNIT
Trigger LED Current	TLP3020	I_{FT}	$V_T=3\text{V}$	—	—	30	mA
	TLP3021			—	—	15	
	TLP3022			—	5	10	
	TLP3023			—	—	5	
Capacitance Input to Output		C_S	$V_S=0, f=1\text{MHz}$	—	0.8	—	pF
Isolation Resistance		R_S	$V_S=500\text{V}$ (R.H. $\leq 60\%$)	5×10^{10}	10^{14}	—	Ω
Isolation Voltage		B_{VS}	AC, 1 minute	—	—	—	V_{rms}
			AC, 1 second (in oil)	—	10000	—	V_{dc}
			DC, 1 minute (in oil)	—	10000	—	


Fig. 1 dv/dt TEST CIRCUIT




$I_F - T_a$




$I_T \text{ (RMS)} - T_a$




$I_{FP} - D_R$




$I_F - V_F$




$\Delta V_F / \Delta T_a - I_F$




$I_{FP} - V_{FP}$




NORMALIZED I_{FT} - T_a




NORMALIZED I_H - T_a



NORMALIZED I_{DRM} - T_a



NORMALIZED V_{DRM} - T_a



NORMALIZED LED CURRENT
- LED CURRENT PULSE WIDTH

